

# LOAN DOCUMENT

		PHOTOGRAPH THIS SHEET		①
DTIC ACCESSION NUMBER		LEVEL		
	ARLCB-TR-83033			
	DOCUMENT IDENTIFICATION Sep 83			
	<b>DISTRIBUTION STATEMENT A</b> Approved for Public Release Distribution Unlimited			
<b>ACCESSION FOR</b> NTIS <input type="checkbox"/> GRAM <input checked="" type="checkbox"/> DTIC <input type="checkbox"/> TRAC <input type="checkbox"/> UNANNOUNCED <input type="checkbox"/> JUSTIFICATION				
BY				
DISTRIBUTION/				
AVAILABILITY CODES				
DISTRIBUTION	AVAILABILITY AND/OR SPECIAL			
A-1		DATE ACCESSIONED		
DISTRIBUTION STAMP				
19990519 147		REGISTERED OR CERTIFIED NUMBER		
DATE RECEIVED IN DTIC				
PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-FDAC				

H  
A  
N  
D  
L  
E  
  
W  
I  
T  
H  
  
C  
A  
R  
E

**TECHNICAL REPORT ARLCB-TR-83033**

**CHARACTERIZATION OF CHYSTALLOGRAPHIC STRUCTURE  
AND INTERNAL STRESS OF CHROMIUM COATINGS  
PLATED UNDER CURRENT INTERRUPTIONS**

**G. P. CAPSIMALIS**

**E. S. CHEN**

**SEPTEMBER 1983**



**US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER  
LARGE CALIBER WEAPON SYSTEMS LABORATORY  
BENET WEAPONS LABORATORY  
WATERVLIET N.Y. 12189**

**APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED**

#### DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacture(s) does not constitute an official indorsement or approval.

#### DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.



## 20. ABSTRACT (CONT'D)

these plating conditions, it was also found that (1) lower amounts of chromium hydride ( $\text{CrH}_x$ ) occur in the deposit, (2) a large decrease in the microcrack density of the deposit occurs, and (3) the deposits tend to become compressively stressed.

## TABLE OF CONTENTS

	<u>Page</u>
ACKNOWLEDGEMENT	11
INTRODUCTION	1
EXPERIMENTAL	2
Determination of Optimum on/Off Duty Cycle	2
STRUCTURAL RESULTS AND DISCUSSION	3
Appearance and Mechanical Properties	3
Texture	3
Residual Stresses	4
Chromium Hydride Phase	5
SUMMARY AND DISCUSSION	6
REFERENCES	8

## LIST OF ILLUSTRATIONS

1. Cathode Potential (With Respect to Standard Calomel Electrode) vs. Time (Charging/Off Time).	9
2. Comparison of Microstructure and Some Other Properties of HC and IC Chromium.	10
3. X-Ray Diffraction Spectra of IC Chromium Plated at 30 A/dm <sup>2</sup> and Various Interrupt Time (IT) Intervals.	11
4. X-Ray Diffraction Spectra of IC Chromium Plated at 45 A/dm <sup>2</sup> and Various Interrupt Time (IT) Intervals.	12
5. X-Ray Diffraction Spectra of IC Chromium Plated at 60 A/dm <sup>2</sup> and at Various Interrupt Time (IT) Intervals.	13

#### ACKNOWLEDGEMENTS

The authors wish to express their appreciation to Dr. I. Ahmad for his encouragement and technical support throughout the course of this project.

## INTRODUCTION

For over 30 years High Contraction (HC) chromium has been used to extend the wear and erosion life of gun barrels. Its attractiveness results from its oxidation resistance and retention of hardness at elevated temperatures and its excellent resistance to friction and wear. The acceptance of electrolytically deposited HC chromium as a good protective coating is limited however, by the large tensile stresses and the well-known crack networks which are always present in the deposit. These two limiting factors being dependent upon the deposition conditions, proved to be the target of numerous investigations. The idea of plating conventional HC crack-free chromium has been reported by Saiddington and Hoey<sup>1</sup> and others.<sup>2-4</sup> Based on the observation that cracks do not form in chromium deposits until a critical thickness of about 0.5  $\mu\text{m}$  is reached, they have demonstrated<sup>1</sup> that by means of controlled current interruptions, the microcracks can be effectively reduced or eliminated. Although there is no simple theory to explain the presence of stresses in electrodeposits, a number of comprehensive reviews<sup>5,6</sup> suggest that their origin is due to the crystal lattice defects which are trapped in the deposit during the electrocrystallization process. Likewise, the evidence from these articles and others suggest that the various plating parameters are the critical factors that control the residual stress of the deposit.

---

<sup>1</sup>J. C. Saiddington and G. R. Hoey, *Plating*, 61, p. 923 (1974).

<sup>2</sup>H. Chessin and E. J. Seyb, Jr., *Plating*, 55, p. 821 (1968).

<sup>3</sup>H. Fry, *Trans. Inst. Met. Finishing*, 32, p. 107, (1955).

<sup>4</sup>W. Blum, *Plating*, 48, p. 613, (1961).

<sup>5</sup>R. Weil, *Plating*, 57, p. 1231 (1970).

<sup>6</sup>J. B. Kushner, *Plating*, 60, p. 1248 (1973).



On the basis of the above evidence, the current work was undertaken to investigate the crystallography and residual stresses in electrodeposited chromium produced as a function of plating variables, as a means of formulating the direction towards property improvements. In particular, the investigation was aimed at the effect of interrupted current (IC) chromium plating at various current densities on the visual crack morphology, crystallographic structure, and residual stress state of the deposit.

## EXPERIMENTAL

A standard plating system was set up in which a Flexopulse periodic current-interruptor made by Rapid Electric was placed in series with the D.C. power supply to allow IC plating using several preselected on/off cycles. All of the IC chromium deposits for this study were prepared using a conventional chromic acid solution which had been aged for 250 A-hr/l and maintained at the composition of 250 g/l  $\text{CrO}_3$  and 2.5 g/l  $\text{H}_2\text{SO}_4$  and a temperature of 55°C. The coatings were deposited on a polished flat sheet of annealed brass substrate and increased to a total chromium thickness of 75  $\mu\text{m}$  which is optimum for x-ray diffraction analysis.

### Determination of Optimum On/Off Duty Cycle

As discussed in the introduction, the effective interruption of current during chromium plating can produce crack-free deposits. This current interruption is responsible for disrupting the cathode film during chromium plating and thus can lead to changes in the deposit properties. The nature of this disruption during IC plating was investigated through polarization measurements using the same type of conventional chromic acid electrolyte at

55°C. The resulting current-voltage relationships shown in Figure 1 indicated that a current interruption of 15 sec duration was necessary to disrupt the cathode film completely. On the basis of these measurements, the on/off duty cycles of 30/5, 30/15, and 30/30 seconds were selected for studying the IC chromium deposits. Additionally, for each of the duty cycles indicated above, IC chromium deposits were prepared at current densities of 30, 45, and 60 A/dm<sup>2</sup>.

## STRUCTURAL RESULTS AND DISCUSSION

### Appearance and Mechanical Properties

A comparison of some of the properties of IC and HC chromium is shown in Figure 2. The surface morphology of this IC chromium deposits was examined by means of a low magnification stereo microscope. The crack pattern of these deposits varied from a crack-free structure to one of heavy crack density. Corresponding to this structure, the hardness was found to vary between 770 and 1100 KHN and the tensile strength between 30.0 and 0 ksi. While a wide range of properties can be attained with IC chromium plating, better results are obtained from deposits plated at the higher current densities and longer interruption times.

### Texture

The x-ray diffraction spectra shown in Figures 3 through 5 have been obtained by means of a diffractometer scan using molybdenum monochromatic radiation. For the sake of convenience these spectra have been organized in Figures 3 through 5 to reflect the changes which occur in the deposited structures as a result of the longer current interruption times and also the

higher current densities. It is clearly seen that for the case of no current interruption, all three current density deposited structures are characterized by the expected and well known  $\langle 111 \rangle$  fiber texture. When the current interruption time is increased, distinct differences in structure among the three current densities are found. For the case of the low current density of  $30 \text{ A/dm}^2$  as seen in Figure 3, increasing the current interruption interval does not affect the characteristic  $\langle 111 \rangle$  preferred orientation of the deposits. As shown in Figure 4 at  $45 \text{ A/dm}^2$  a noticeable disturbance of the  $\langle 111 \rangle$  preferred orientation occurred as the current was interrupted at the various duty cycles. As a result of the changes in intensities of the x-ray lines observed in Figure 4, it was deduced that a small fraction of the chromium crystallites grown in these deposits departed from the common  $\langle 111 \rangle$  direction to random orientations and favored especially the  $\langle 211 \rangle$  direction. As shown in Figure 5 at  $60 \text{ A/dm}^2$ , the current interruption produced deposits with a dual  $\langle 211 \rangle$  and  $\langle 111 \rangle$  fiber texture. Again from a comparison of the intensities observed the  $\langle 211 \rangle$  texture of these deposits was stronger than the  $\langle 111 \rangle$  texture, implying that a larger number of crystallites with the  $\langle 211 \rangle$  rather than the  $\langle 111 \rangle$  preferred orientation, have competitively grown parallel to the deposit surface. A comparison of intensities in Figures 4 and 5 showed that a greater fraction of the crystallites became random as the current density was increased from 45 to  $60 \text{ A/dm}^2$ .

#### Residual Stresses

Residual stresses in the IC chromium deposits were measured by means of an automated computer controlled x-ray diffraction system we developed and

reported earlier.<sup>7</sup> Typically, the chromium deposit stresses varied from tensile stresses of 15 ksi to compressive stresses of 30 ksi. Regarding the stress measurements however, it should be noted that for the deposits with large microcrack densities the results were scattered and not always meaningful. The x-ray stress data had to be carefully interpreted to eliminate the effects of texture and high stress gradients that are present across the thickness of the deposits. In general, the high compressive stresses were measured from practically crack free samples that were deposited at the high interruption cycles and the current density of 60 A/dm<sup>2</sup>.

#### Chromium Hydride Phase

As a consequence of the x-ray residual stress measurements it was found that an additional non-equatorial reflection occurred which did not belong in the bcc chromium structure, but satisfied the angular position of chromium hydride in the form CrH<sub>x</sub>. Assuming that the chromium hydride phase has a preferred orientation as most other electrodeposits, this peak found off the equatorial direction provided a way of measuring qualitatively the retained chromium hydride in the IC chromium deposits. On the basis of the above findings our x-ray measurements on the IC chromium deposits show that CrH<sub>x</sub> is almost always present at low current densities with no current interruption, and decreases significantly as the interruption time and current density reach their high values.

---

<sup>7</sup>G. P. Capsimalis, R. F. Haggerty, and K. Loomis, "Computer Controlled X-Ray Stress Analysis for Inspection of Manufactured Components," WVT-TR-77001, Watervliet Arsenal, Watervliet, NY, January 1977.

## SUMMARY AND DISCUSSION

Several of our results are similar to those previously reported. In particular, the deposition of crack-free chromium by means of current interruptions is well documented.<sup>1-4</sup> The present study extends these earlier findings in providing more specific information on the effect of current interruption cycles and current density on the crystal structure and internal stress of the chromium deposits. While varying the on/off duty plating cycle and current density deposits with very different structures and properties have been observed. As a rule we found that increasing the current density to 60 A/dm<sup>2</sup> and the interruption interval to 30 sec have resulted in deposits with lower microcrack densities and improved mechanical properties. It was also found that uninterrupted deposits have a very strong  $\langle 111 \rangle$  fiber texture while for high interruption times and 60 A/dm<sup>2</sup> current density, the  $\langle 111 \rangle$  fiber texture is diminished considerably and the  $\langle 211 \rangle$  orientation becomes dominant. Additionally, our measurements show that along with these changes there is a decrease in the chromium hydride retained in the deposit. The above evidence suggest a mechanism in which the crystallites with growth cones in the  $\langle 111 \rangle$  direction preferentially trap the chromium hydride during coalescence. As the deposit becomes more random or tends towards the  $\langle 211 \rangle$  texture less of the hydride phase is retained. The chromium hydride phase has a larger unit cell than bcc chromium and is unstable; and its decomposition

---

<sup>1</sup>J. C. Saiddington and G. R. Hoey, *Plating*, 61, p. 923 (1974).

<sup>2</sup>H. Chessin and E. J. Seyb, Jr., *Plating*, 55, p. 821 (1968).

<sup>3</sup>H. Fry, *Trans. Inst. Met. Finishing*, 32, p. 107, (1955).

<sup>4</sup>W. Blum, *Plating*, 48, p. 613, (1961).

has been considered for a long time as being responsible for the presence of cracks in electrodeposited chromium.

Finally, the residual stresses measured were found to correlate best with electrodeposition rate due to current density and the orientation textures due to the interruption cycle.

## REFERENCES

1. J. C. Saiddington and G. R. Hoey, *Plating*, 61, p. 923 (1974).
2. H. Chessin and E. J. Seyb, Jr., *Plating*, 55, p. 821 (1968).
3. H. Fry, *Trans. Inst. Met. Finishing*, 32, p. 107 (1955).
4. W. Blum, *Plating*, 48, p. 613 (1961).
5. R. Weil, *Plating*, 57, p. 1231 (1970).
6. J. B. Kushner, *Plating*, 60, p. 1248 (1973).
7. G. P. Capsimalis, R. F. Haggerty, and K. Loomis, "Computer Controlled X-Ray Stress Analysis for Inspection of Manufactured Components," WVT-TR-77001, Watervliet Arsenal, Watervliet, NY, January 1977.




Figure 1. Cathode Potential (with respect to Standard Calomel Electrode) vs. Time (Charging /off Time).




STANDARD HARD CHROME (HC)



1000X

INTERRUPTED PLATED CHROME (IC)



1000X

	HC Chrome	IC Chrome
Bath Temperature °C	55	55
Current Density (A/dm <sup>2</sup> )	30	35
Plating Rate (Mils/Hrs)	1	0.5
Hardness (KHN)	940	790
UTS (Psi)	15,000	30,000

Fig. 2. Comparison of Microstructure and Some Other Properties of HC and IC Chromium.




Fig. 3. X-Ray Diffraction Spectra of IC Chromium Plated at 30 A/dm<sup>2</sup> and Various Interrupt Time (IT) Intervals.




Fig. 4. X-Ray Diffraction Spectra of IC Chromium Plated at 45 A/dm<sup>2</sup> and Various Interrupt Time (IT) Intervals.




Fig. 5. X-Ray Diffraction Spectra of IC Chromium Plated at 60 A/dm<sup>2</sup> and at Various Interrupt Time (IT) Intervals.

## READER EVALUATION

Please take a few minutes to complete the questionnaire below and return to us at the following address: Commander, Armament Research and Development Center, U.S. Army AMCCOM, ATTN: Technical Publications, DRSMC-LCB-TL, Watervliet, NY 12189.

1. Benet Weapons Lab. Report Number \_\_\_\_\_

2. Please evaluate this publication (check off one or more as applicable).

	Yes	No
Information Relevant	_____	_____
Information Technically Satisfactory	_____	_____
Format Easy to Use	_____	_____
Overall, Useful to My Work	_____	_____
Other Comments	_____	

3. Has the report helped you in your own areas of interest? (i.e. preventing duplication of effort in the same or related fields, savings of time, or money). \_\_\_\_\_

4. How is the report being used? (Source of ideas for new or improved designs. Latest information on current state of the art, etc.). \_\_\_\_\_

5. How do you think this type of report could be changed or revised to improve readability, usability? \_\_\_\_\_

6. Would you like to communicate directly with the author of the report regarding subject matter or topics not covered in the report? If so please fill in the following information.

Name: \_\_\_\_\_

Telephone Number: \_\_\_\_\_

Organization Address: \_\_\_\_\_

# TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
ASST SEC OF THE ARMY RESEARCH & DEVELOPMENT ATTN: DEP FOR SCI & TECH THE PENTAGON WASHINGTON, D.C. 20315	1	COMMANDER US ARMY AMCCOM ATTN: DRSMC-LEP-L(R) ROCK ISLAND, IL 61299	1
COMMANDER DEFENSE TECHNICAL INFO CENTER ATTN: DTIC-DDA CAMERON STATION ALEXANDRIA, VA 22314	12	COMMANDER ROCK ISLAND ARSENAL ATTN: SMCRI-ENM (MAT SCI DIV) ROCK ISLAND, IL 61299	1
COMMANDER US ARMY MAT DEV & READ COMD ATTN: DRCDE-SG 5001 EISENHOWER AVE ALEXANDRIA, VA 22333	1	DIRECTOR US ARMY INDUSTRIAL BASE ENG ACTV ATTN: DRXIB-M ROCK ISLAND, IL 61299	1
COMMANDER ARMAMENT RES & DEV CTR US ARMY AMCCOM ATTN: DRSMC-LC(D) DRSMC-LCE(D) DRSMC-LCM(D) (BLDG 321) DRSMC-LCS(D) DRSMC-LCU(D) DRSMC-LCW(D) DRSMC-SCM-O (PLASTICS TECH EVAL CTR, BLDG. 351N) DRSMC-TSS(D) (STINFO) DOVER, NJ 07801	1 1 1 1 1 1 1 2	COMMANDER US ARMY TANK-AUTMV R&D COMD ATTN: TECH LIB - DRSTA-TSL WARREN, MI 48090	1
DIRECTOR BALLISTICS RESEARCH LABORATORY ARMAMENT RESEARCH & DEV CTR US ARMY AMCCOM ATTN: DRSMC-TSB-S (STINFO) ABERDEEN PROVING GROUND, MD 21005	1	COMMANDER US ARMY TANK-AUTMV COMD ATTN: DRSTA-RC WARREN, MI 48090	1
MATERIEL SYSTEMS ANALYSIS ACTV ATTN: DRXSY-MP ABERDEEN PROVING GROUND, MD 21005	1	COMMANDER US MILITARY ACADEMY ATTN: CHMN, MECH ENGR DEPT WEST POINT, NY 10996	1
		US ARMY MISSILE COMD REDSTONE SCIENTIFIC INFO CTR ATTN: DOCUMENTS SECT, BLDG. 4484 REDSTONE ARSENAL, AL 35898	2
		COMMANDER US ARMY FGN SCIENCE & TECH CTR ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	1

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH AND DEVELOPMENT CENTER,  
US ARMY AMCCOM, ATTN: BENET WEAPONS LABORATORY, DRSMC-LCB-TL,  
WATERVLIET, NY 12189, OF ANY ADDRESS CHANGES.

# TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT'D)

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
COMMANDER		DIRECTOR	
US ARMY MATERIALS & MECHANICS		US NAVAL RESEARCH LAB	
RESEARCH CENTER	2	ATTN: DIR, MECH DIV	1
ATTN: TECH LIB - DRXMR-PL		CODE 26-27, (DOC LIB)	1
WATERTOWN, MA 01272		WASHINGTON, D.C. 20375	
COMMANDER		COMMANDER	
US ARMY RESEARCH OFFICE		AIR FORCE ARMAMENT LABORATORY	
ATTN: CHIEF, IPO	1	ATTN: AFATL/DLJ	1
P.O. BOX 12211		AFATL/DLJG	1
RESEARCH TRIANGLE PARK, NC 27709		EGLIN AFB, FL 32542	
COMMANDER		METALS & CERAMICS INFO CTR	
US ARMY HARRY DIAMOND LAB		BATTELLE COLUMBUS LAB	1
ATTN: TECH LIB	1	505 KING AVENUE	
2800 POWDER MILL ROAD		COLUMBUS, OH 43201	
ADELPHIA, MD 20783			
COMMANDER			
NAVAL SURFACE WEAPONS CTR			
ATTN: TECHNICAL LIBRARY	1		
CODE X212			
DAHLGREN, VA 22448			

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH AND DEVELOPMENT CENTER,  
US ARMY AMCCOM, ATTN: BENET WEAPONS LABORATORY, DRSMC-LCB-TL,  
WATERVLIET, NY 12189, OF ANY ADDRESS CHANGES.

# TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
CHIEF, DEVELOPMENT ENGINEERING BRANCH	
ATTN: DRSMC-LCB-D	1
-DP	1
-DR	1
-DS (SYSTEMS)	1
-DS (ICAS GROUP)	1
-DC	1
CHIEF, ENGINEERING SUPPORT BRANCH	
ATTN: DRSMC-LCB-S	1
-SE	1
CHIEF, RESEARCH BRANCH	
ATTN: DRSMC-LCB-R	2
-R (ELLEN FOGARTY)	1
-RA	1
-RM	1
-RP	1
-RT	1
TECHNICAL LIBRARY	5
ATTN: DRSMC-LCB-TL	
TECHNICAL PUBLICATIONS & EDITING UNIT	2
ATTN: DRSMC-LCB-TL	
DIRECTOR, OPERATIONS DIRECTORATE	1
DIRECTOR, PROCUREMENT DIRECTORATE	1
DIRECTOR, PRODUCT ASSURANCE DIRECTORATE	1

NOTE: PLEASE NOTIFY DIRECTOR, BENET WEAPONS LABORATORY, ATTN: DRSMC-LCB-TL,  
OF ANY ADDRESS CHANGES.